LiuGong

CLG2035H

C


POWER TYPE	BASE CAPACITY	LOAD CENTER	SERVICE WEIGHT
Diesel	@RATED LOAD CENTER 7,000 LBS/3,500 KG	24 IN/500 MM	10,450 LBS /4,750 KG




XTRACARE
WARRANTY

CLG2035H SPECIFICATIONS >>>

General	Model				CLG2035H		
	Power Type	1			Diesel		
	Units	2			Imperial		Metric
	Base Capacity	3	@Rated load center	lbs	7,000	kg	3,500
	Load Center	4		in	24	mm	500
Weights	Service Weight	5	Unloaded	lbs	10,450	kg	4,750
	Axle Load	6	Loaded/Unloaded,Front	lbs	15,880/3,744	kg	7,218/1,702
		7	Loaded/Unloaded,Rear	lbs	2,270/6,706	kg	1,032/3,048
Tires	Tire Type	8			Pneumatic		
	Wheels	9	Front/Rear		2/2		
	Wheelbase	10		in	66.9	mm	1700
	Tire Size	11	Front		28x9-15-14PR		
		12	Rear		6.50-10-10PR		
	Tread Width	13	Front/Rear	in	39.4/38.8	mm	1000/985
Mast	Max.Fork Height	14	With std 2-stage mast	in	118.1	mm	3,000
	Free lift	15	With std 2-stage mast	in	3.9	mm	100
	Height,Upright Lowered	16	With std 2-stage mast	in	84.6	mm	2,150
	Height,Upright Extended	17	With std 2-stage mast	in	164.6	mm	4,182
	Mast Tilt,Fwd/Back	18	With std 2-stage mast	deg	6°/12°		
	Carriage	19	Width	in	43.3	mm	1,100
	Fork Spread	20	Minimum/Maximum	in	9.6/42.2	mm	244/1,072
	Fork Dimensions	21	TxWxL	in	2×4.8×42.1	mm	50x122x1,070
Chassis	Length to Fork Face	22	With std 2-stage mast	in	107.8	mm	2,738
	Overall Width	23		in	48.2	mm	1,225
	Overhead Guard Height	24		in	86.6	mm	2,200
	Turning Radius	25	Minimum outside	in	95.9	mm	2,435
	Fork Overhang	26	With std 2-stage mast	in	18.9	mm	480
	Right Angle Stack	27	Includes load length and clearance	in	160.4	mm	4,075
	Ground Clearance	28	Loaded below mast	in	5.1	mm	130
		29	Center of wheelbase	in	6.5	mm	165
Performance	Travel Speed	30	Loaded/Unloaded	mph	10.9/11.5	km/h	17.5/18.5
	Lift Speed	31	Loaded/Unloaded	fpm	101/110	mm/s	505/550
	Lower Speed	32	Loaded/Unloaded	fpm	101/83	mm/s	505/415
	Max.Drawbar Pull	33	Loaded	lbs	5060	kg	2,300
	Max.Gradeability	34	Loaded/Unloaded	%	24/25		
Systems	Brakes	35	Service		Foot/Hyd		
		36	Parking		Hand/Mech		
	Engine	37	Manufacturer		Kubota		
		38	Model		V2403-CR-TE5B		
		39	Emission compliance		EU Stage V		
		40	Cylinders		4		
		41	Displacement	Liters	2.434		
		42	Rated power	Hp/rpm	58.8/2,400	kW/rpm	43.2/2,400
		43	Max.torque	N·m/rpm	198.5/1,500		





Specifications and designs are subject to change without notice.
Machines shown may clude optional equipment.

LiuGong Construction Machinery N.A.LLC. T:281-579-8882 F:281-579-8388
22220 Merchants Way-Suite 100 www.liugongna.com
Katy,TX 77449
USA