LiuGong

CLG2030G

G


POWER TYPE	BASE CAPACITY	LOAD CENTER	SERVICE WEIGHT
Gas/LPG	@RATED LOAD CENTER 6,600 LBS/3,000 KG	20 IN/500 MM	9,768 LBS/4,440 KG




XTRACARE
WARRANTY

CLG2030G SPECIFICATIONS >>>

GENERAL	Model				CLG2030G		
	Power Type	1			Gas/LPG		
	Units	2		Imperial		Metric	
	Base Capacity	3	@Rated load center	lbs	6600	kg	3,000
	Load Center	4		in	20	mm	500
WEIGHTS	Service Weight	5	Unloaded	lbs	9,768	kg	4,440
	Axle Load	6	Loaded/Unloaded,Front	lbs	14,227/3,843	kg	6,467/1,747
		7	Loaded/Unloaded,Rear	lbs	2,140/5,925	kg	973/2,693
TIRES	Tire Type	8			Pneumatic		
	Wheels	9	Front/Rear		2/2		
	Wheelbase	10		in	66.9	mm	1700
	Tire Size	11	Front		28x9-15-14PR		
		12	Rear		6.50-10-10PR		
	Tread Width	13	Front/Rear	in	39.4/38.8	mm	1000/985
MAST	Max.Fork Height	14	With std 2-stage mast	in	118.1	mm	3,000
	Free lift	15	With std 2-stage mast	in	5.7	mm	145
	Height,Upright Lowered	16	With std 2-stage mast	in	82.9	mm	2,105
	Height,Upright Extended	17	With std 2-stage mast	in	164.6	mm	4,182
	Mast Tilt,Fwd/Back	18	With std 2-stage mast	deg	6°/12°		
	Carriage	19	Width	in	43.3	mm	1,100
	Fork Spread	20	Minimum/Maximum	in	9.6/42.2	mm	244/1,072
	Fork Dimensions	21	TxWxL	in	1.6×4.8×42.1	mm	45x122x1,070
CHASSIS	Length to Fork Face	22	With std 2-stage mast	in	105.8	mm	2,688
	Overall Width	23		in	48.2	mm	1,225
	Overhead Guard Height	24		in	86.6	mm	2,200
	Turning Radius	25	Minimum outside	in	94.5	mm	2,400
	Fork Overhang	26	With std 2-stage mast	in	18.7	mm	475
	Right Angle Stack	27	Includes load length and clearance	in	160.4	mm	4,075
	Ground Clearance	28	Loaded below mast	in	5.1	mm	130
		29	Center of wheelbase	in	6.5	mm	165
PERFORMANCE	Travel Speed	30	Loaded/Unloaded	mph	11.5/11.8	km/h	18.5/19
	Lift Speed	31	Loaded/Unloaded	fpm	110/114	mm/s	550/570
	Lower Speed	32	Loaded/Unloaded	fpm	101/83	mm/s	505/415
	Max.Drawbar Pull	33	Loaded	lbs	4,620	kg	2,100
	Max.Gradeability	34	Loaded/Unloaded	%	24/26		
SYSTEMS	Brakes	35	Service		Foot/Hyd		
		36	Parking		Hand/Mech		
	Engine	37	Manufacturer		Kubota		
		38	Model		WJ2503-L-E3		
		39	Emission compliance		EU Stage V/EPA		
		40	Cylinders		4		
		41	Displacement	Liters	2.491		
		42	Rated power	Hp/rpm	55.3/2,600	kW/rpm	41.3/2,600
		43	Max.torque	N·m/rpm	175/1,200(LPG)	167.6/1,800(GAS)	





Specifications and designs are subject to change without notice.
Machines shown may"clude optional equipment.

LiuGong Construction Machinery N.A.LLC. T:281-579-8882 F:281-579-8388
22220 Merchants Way-Suite 100 www.liugongna.com
Katy,TX 77449
USA